



## PC 6

A compact, light-weight entry in the Point Concentric series, the PC 6 fits well into many applications with its 70° conical pattern. It ships with standard M10 fly points and also has Omni Mount 20 series mounting points and is designed to produce linear, high resolution audio throughout its intended bandwidth.

The Point Concentric 6 houses a single coaxial driver and is suitable for smaller live performances as a stand-alone enclosure, as well as a variety of fill applications.

All Point Concentric enclosures are constructed of 12 mm Baltic Birch, rather than moulded plastic or fiberglass, resulting in a lower resonant frequency.

### Specifications

Frequency Range (-10 dB)	82 Hz - 18 kHz
Nominal Directivity (-6 dB) H x V	70° x 70°
Maximum Peak SPL**	125 dB
Components LMF / HF	B&C 6FH51 6.5" Coaxial Driver
Nominal Impedance Passive	6 Ω
Power Handling (AES / Peak) LF	150 / 600 W
Power Handling (AES / Peak) HF	10 / 40 W
Power Handling (AES / Peak) Passive	160 / 640 W
Rigging	2x Mini SLR™ Socket (M10) Omni Mount 20 Series with 1/4 - 20 Screws
Connection	2x Speakon™ NL4
Height Front (mm / in)	280 / 11.05
Width (mm / in)	201 / 7.9
Depth (mm / in)	209 / 8.25
Weight (kg / lbs)	5.5 / 12
Processing	Lake, IPD

\*\*12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

